

DECLARATION OF PERFORMANCE

DoP No. 1020-CPR-090-043536 - GB

(Version 1)

To see the previous versions of DoP, click on: http://dop-fixings.com/SPIT/DOP_SPIT archives/Dop_GB archives.zip

- 1. Unique identification code of the product-type: SPIT PTH-SX
- 2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

ETA-18/1101 (07/02/2019), Batch number: see packaging of the product.

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Generic type	Nailed-in plastic anchor (plate)
For use in	Concrete and masonry for fixing of external insulation composite systems with rendering Ø8 Concrete C12/15 to C50/60 Masonry: Clay bricks, perforated clay bricks, solid bricks
Option / Category	A,B,C,D,E
Loading	Static and quasi static
Material	Anchor sleeve: Polypropylene copolymer - Expansion screw: Glass fiber reinforced polyamide
Temperature range if applicable	

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

SPIT - Route de Lyon - 26501 Bourg Les Valence - France

- 5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2): --
- 6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 2+**
- 7. In case of the declaration of performance concerning a construction product covered by a harmonised standard: --

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

TZUS Technický a zkušební ústav stavební Praha, s.p., Prosecká 811/76a, 190 00 Praha 9 - Prosek issued ETA-18/1101 (07/02/2019)

on the basis of EAD 330196-01-0604,

The notified body 1020-CPR performed under System 2+

- i. Determination of the product type on the basis of type testing (including sampling), type calculation, tabulated values or descriptive documentation of the product;
- ii. Initial inspection of the manufacturing plant and of factory production control;
- iii. Continuous surveillance, assessment and evaluation of factory production control under system1

9. Declared performance:

Essential Characteristics	Design Method	Performance	Harmonized Technical Specification
characteristic resistance for tension	EN 1992-1-1	ETA-18/1101 Annex C1 ETA-18/1101 ETA-18/1101	
characteristic resistance for shear	EAD 330196-00-0604	NPD ETA-18/1101 ETA-18/1101	
minimum spacing and minimum edge distance	EN 1992-1-1	ETA-18/1101 Annex B5 ETA-18/1101	EAD 330196- 01-0604
displacement for serviceability limit state	EN 1992-1-1	ETA-18/1101 Annex C1 ETA-18/1101 ETA-18/1101	

Where pursuant to Article 37 or 38 in the Specific Technical Documentation has been used, the requirements with which the product complies: --

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Bourg-Lés-Valence (France), 11/03/2019

G. HILDENBRAND

Product Marketing & Development Director

A. AUBIER

Operations Director, Continental Europe Division

